

## Centrifugal Monoblock Pumps

**Approximate Performance Chart at 50 Hz., 230 V (±10%) for Single Phase, 415V(-15% & +6%), Three Phase 2880 RPM**

MODEL	MOTOR RATING		PIPE SIZE (MM)	Head in Mtr.															
	HP	KW		4	5	6	8	9	10	12	14	16	18	20	22	24	26	28	
				Discharge in LPM															
VMC 10	0.5	0.37	25 X 25				130	128	125	115	95	65	40						
VMC 11	0.5	0.37	40 X 40			270	235	218	205	110									
VMC 11 H	0.5	0.37	40 X 40				270	250	230	170	70								
VHC 12	0.5	0.37	50 X 50		335	300	240	200	150										
VMC 23	1	0.75	25 X 25									160	150	140	130	110	90	60	
VMC 25	1	0.75	40 X 40					270	255	230	210	185	150	110					
VMC 26	1	0.75	50 X 40				300	290	270	250	230	180							
VMC 13	1	0.75	50 X 50			500	480	440	425	300									
VMC 14	1	0.75	75 X 75		800	700	400	150											
VMC 15	1.5	1.1	50 X 50				470	460	440	365	235								
VMC 16	1.5	1.1	65 X 50					480	460	400	360	270	180						
VMC 21	1.5	1.1	75 X 75		900	800	600	350	150										
VMC 21 H	1.5	1.1	75 X 75			900	750	680	600	460	360(13m)								
VMC 17	2	1.5	50 X 50				500	450	440	415	385	340	300	215	195	140(23m)			
VMC 17 N	2	1.5	50 X 50				480	420	410	385	360	320	282	200	180	115(23m)			
VMC 18	2	1.5	65 X 50			625	590	575	540	490	460	380	320	250					
VMC 18 N	2	1.5	65 X 50			590	550	535	500	455	425	350	295	230					
VMC 19	2	1.5	75 X 75			1000	900	790	700	530									
VMC 19 H	2	1.5	75 X 75					835	740	635	525	380	180						
VMC 20	2	1.5	75 X 65			700	620	590	550	495	390	200							
VMC 24	2	1.5	100 X 100	1150	1040	980	840	750	660	440									
VMC 27	3	2.2	65 X 50						570	540	500	475	450	420	380	300	250		
VMC 28	3	2.2	100 X 100		1100	1000	900	800	700	530	250(23m)								

